



### Bearing No. 6022

D	170 mm
d	110 mm
B	28 mm
C	28 mm
f0	15.6
Cu	3.55
Cr	103
C0r	73.0
Bore	4.331 Inch   110 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	1,96 Kg
r(min)	2
r min.	2 mm
da min.	119 mm
ra(max)	2
Da max.	161 mm
Da(max)	161
da(min)	119
ra max.	2 mm
Category	Single Row Ball Bearing
Oil lub.	4500
Inventory	0.0
Enclosure	Open
Size (mm)	110x170x28
Snap Ring	No
Width (mm)	28
Grease lub.	3800
Bearing No.	6022

Weight / LBS	4.673
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6022
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outer Race Width	1.102 Inch   28 Millimeter
Long Description	110MM Bore; 170MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	6.693 Inch   170 Millimeter
(Refer.)Mass(kg)	1.96
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Weight / Kilogram	2.122
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	4500 r/min
Manufacturer Item Number	6022
Internal Special Features	No
(Grease) Lubrication Speed	3800 r/min

Basic static load rating (C0)	73 kN
Basic dynamic load rating (C)	82 kN
Maximum Capacity / Filling Slot	No