



Bearing No. 232/530 CA/W33

K	12 mm
d	530 mm
D	980 mm
B	355 mm
b	22.3 mm
Size (mm)	980x530x355
Width (mm)	355
Mass bearing	1200 kg
d2	670 mm
D1	836 mm
Limiting speed	480 r/min
Bearing number	232/530 CA/W33
Reference speed	320 r/min
ra max.	8 mm
Da max.	940 mm
Bore Diameter (mm)	980
da min.	570 mm
Outer Diameter (mm)	530
da - min.	570 mm
Da - max.	940 mm
ra - max.	8 mm
Calculation factor e	0.35
r1,2 min.	9.5 mm
D1 ?	836 mm
d2 ?	670 mm
Calculation factor - e	0.35
r1,2 - min.	9.5 mm
Basic dynamic load rating C	13268 kN
Basic dynamic load	13268 kN

rating - C Fatigue load	
limit Pu	1220 kN
Calculation factor Y1	1.9
Calculation factor Y2	2.9
Calculation factor Y0	1.8
Calculation factor - Y0	1.8
Calculation factor - Y2	2.9
Calculation factor - Y1	1.9
Fatigue load limit - Pu	1220 kN
Basic static load rating C0	20400 kN
Basic static load rating - C0	20400 kN